TP-LINK®

User Guide

M5360

3G Mobile Wi-Fi, 5200mAh Power Bank



REV 1.2.0 1910011280

COPYRIGHT & TRADEMARKS

Specifications are subject to change without notice. **TP-LINK**[®] is a registered trademark of TP-LINK TECHNOLOGIES CO., LTD. Other brands and product names are trademarks or registered trademarks of their respective holders.

No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK TECHNOLOGIES CO., LTD. Copyright © 2015 TP-LINK TECHNOLOGIES CO., LTD. All rights reserved.

http://www.tp-link.com

FCC STATEMENT

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/ TV technician for help.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

This device may not cause harmful interference.

This device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: The manufacturer is not responsible for any radio or TV interference caused by unauthorized modifications to this equipment. Such modifications could void the user's authority to operate the equipment.

FCC RF Radiation Exposure Statement:

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. End users must follow the specific operating instructions for satisfying RF exposure compliance. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. This equipment has been SAR-evaluated for use in hand. SAR measurements are based on a 5mm spacing from the body and that compliance is achieved at that distance.

CE Mark Warning

CE1588

This is a class B product. In a domestic environment, this product may cause radio interference, in which case the user may be required to take adequate measures.

Canadian Compliance Statement

This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions:

(1)This device may not cause interference, and

(2)This device must accept any interference, including interference that may cause undesired operation of the device.

Cet appareil est conforme aux norms CNR exemptes de licence d'Industrie Canada. Le fonctionnement est soumis aux deux conditions suivantes:

(1)cet appareil ne doit pas provoquer d'interférences et

(2)cet appareil doit accepter toute interférence, y compris celles susceptibles de provoquer un fonctionnement non souhaité de l'appareil.

Industry Canada Statement

Complies with the Canadian ICES-003 Class B specifications.

Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.

This device complies with RSS 210 of Industry Canada. This Class B device meets all the requirements of the Canadian interference-causing equipment regulations.

Cet appareil numérique de la Classe B respecte toutes les exigences du Règlement sur le matériel brouilleur du Canada.

Korea Warning Statements:

당해 무선설비는 운용중 전파혼신 가능성이 있음.

NCC Notice & BSMI Notice

注意!

依據 低功率電波輻射性電機管理辦法

第十二條 經型式認證合格之低功率射頻電機,費經許可,公司、商號或使用者均不得擅自變更頻 率、加大功率或變更原設計之特性或功能。

第十四條 低功率射頻電機之使用不得影響飛航安全及干擾合法通行; 經發現有干擾現象時, 應立 即停用, 并改善至無干擾時方得繼續使用。前項合法通信, 指依電信規定作業之無線電信。低功率 射頻電機需忍受合法通信或工業、科學以及醫療用電波輻射性電機設備之干擾。 減少電磁波影響, 請妥適使用。 安全諮詢及注意事項

- 請使用原裝電源供應器或只能按照本產品注明的電源類型使用本產品。
- 清潔本產品之前請先拔掉電源線。請勿使用液體、噴霧清潔劑或濕布進行清潔。
- 注意防潮,請勿將水或其他液體潑灑到本產品上。
- 插槽與開口供通風使用,以確保本產品的操作可靠並防止過熱,請勿堵塞或覆蓋開口。
- 請勿將本產品置放於靠近熱源的地方。除非有正常的通風,否則不可放在密閉位置中。
- 請不要私自打開機殼,不要嘗試自行維修本產品,請由授權的專業人士進行此項工作。



Продукт сертифіковано згідно с правилами системи УкрСЕПРО на відповідність вимогам нормативних документів та вимогам, що передбачені чинними законодавчими актами України.

EHC

Safety Information

- When product has power button, the power button is one of the way to shut off the product;
 When there is no power button, the only way to completely shut off power is to disconnect the product or the power adapter from the power source.
- Don't disassemble the product, or make repairs yourself. You run the risk of electric shock and voiding the limited warranty. If you need service, please contact us.
- Avoid water and wet locations.

This product can be used in the following countries:

AT	BG	BY	CA	CZ	DE	DK	EE
ES	FI	FR	GB	GR	HU	E	IT
LT	LV	MT	NL	NO	PL	PT	RO
RU	SE	SK	TR	UA	US		

DECLARATION OF CONFORMITY

For the following equipment:

Product Description: 3G Mobile Wi-Fi, 5200mAh Power Bank

Model No.: M5360

Trademark: TP-LINK

We declare under our own responsibility that the above products satisfy all the technical regulations applicable to the product within the scope of Council Directives:

Directives 1999/5/EC, Directives 2004/108/EC, Directives 2006/95/EC, Directives 1999/519/EC, Directives 2011/65/EU

The above product is in conformity with the following standards or other normative documents **EN 300 328 V1.8.1**

EN 301 489-1 V1.9.2 & EN 301 489-17 V2.2.1 EN 55022: 2010 + AC: 2011 EN 55024: 2010 EN 61000-3-2: 2006 + A1: 2009 + A2: 2009 EN 61000-3-3: 2013 EN 60950-1: 2006 + A11: 2009 + A1: 2010 + A12: 2011

EN 50566: 2013

The product carries the CE Mark:



Person responsible for marking this declaration:

Yang Hongliang Product Manager of International Business

Date of issue: 2015

TP-LINK TECHNOLOGIES CO., LTD.

Building 24 (floors 1, 3, 4, 5), and 28 (floors 1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China

CONTENTS

Package	Conter	nts	1				
Chapter 1	l. In	troduction	2				
1.1	Produc	t Overview	2				
1.2	Main F	eatures	2				
1.3	Physic	al Description	2				
Chapter 2	2. Ha	ardware Installation	5				
2.1	Enviror	nment Requirements	5				
2.2	Hardwa	are Installation	5				
Chapter 3	3. Q	uick Installation Guide	8				
3.1	System	n Requirements	8				
3.2	TCP/IP	Configuration	8				
3.3	Conne	ct to the Internet	8				
3.4	Quick S	Setup	9				
Chapter 4	1. D	evice Configuration	13				
4.1	Status		13				
4.2	Wizard	l	14				
4.3	SMS		14				
	4.3.1	New Message	14				
	4.3.2	Inbox	15				
	4.3.3	Outbox	16				
	4.3.4	Drafts	17				
	4.3.5	SMS Settings					
4.4	Advand	ced	19				
	4.4.1	Dial-up	19				
	4.4.2	Wireless	25				
		DHCP Server					
		System Tools					
••		Q					
	Appendix B: Configuring the PC						
Appendix	C: Spo	ecifications					
Appendix	D: Glo	ossary	44				

Package Contents

The following items should be found in your package:

- > M5360 3G Mobile Wi-Fi, 5200mAh Power Bank
- > One micro USB cable
- Quick Installation Guide
- > Micro/Nano to Standard SIM Card Adapter

P Note:

Make sure that the package contains the above items. If any of the listed items is damaged or missing, please contact your distributor.

Conventions

The Device or M5360 mentioned in this guide stands for M5360 3G Mobile Wi-Fi, 5200mAh Power Bank without any explanation.

Chapter 1. Introduction

1.1 Product Overview

TP-LINK's M5360 is at the forefront of wireless 3G sharing. Equipped with a built-in 3G modem, you can instantly establish your own Wi-Fi hotspot simply by inserting a 3G SIM card at the interior of the device. With up to 21.6Mbps download and 5.76Mbps upload speeds, M5360 is able to provide 3G wireless sharing to up to 10 users simultaneously. Its pocket-sized design and powerful 5200mAh internal battery make it an ideal travel companion, allowing users to work or play for hours on end. Besides, with its innovative OLED display, users can have a much more intuitive view of the device's working status, such as signal strength, network type (2G/3G), Wi-Fi status, message, internet status and battery meter.

1.2 Main Features

- > Equipped with a built-in 3G modem No other bulky devices required
- > HSPA+ supported with up to 21.6Mbps download and 5.76Mbps upload speeds
- > Supports up to 10 users simultaneously
- > Power Bank for charging smart phones and tablets
- > 5200mAh internal battery for extended hours of outdoor use
- Micro USB port for versatile recharging
- > OLED display provides an intuitive view of the device's working status
- > Equipped with a micro SD card slot for up to 32GB of optional storage

1.3 Physical Description




Figure 1-1 the Exterior

The details about the Exterior are explained as below.

> OLED Screen:




Figure 1-2 OLED Screen

The OLED Indication:

ltem	Description	Indication
³ q _{ı /} 2q _ı ∕ R _ı	Network type & Signal strength	Indicates the current network option: 2G /3G /Roam, and signal strength of current network.
\mathbf{S}	Internet connection	Indicates the successful network connection.
M / A	Dial-up type	 Means the automatic mode of Internet connection; Means the manual mode of Internet connection.
WiFi	Wi-Fi connection	Displays the Wi-Fi status and the amount of current wireless clients.
5	SMS	Indicates that there is un-read short message(s) and the amount of un-read messages.
	Battery	Displays the remaining battery power.
0.0B/s↓	Download speed	Indicates the download speed of current data transmission.
0.0B/s†	Upload speed	Indicates the upload speed of current data transmission.
0.0B	Data statistics	Indicates the data used in total. The data statistics will be cleared after resetting the Device.

Table 1-1 The OLED Screen details

PNote:

When you leave alone the buttons on the device, the OLED screen will light on for 60 seconds and then turn off. Pressing the power button will light up or turn off the OLED screen.

- Micro USB Port: It's for you to connect the Device with the power adapter via the USB cable.
- Power Button: When the Device is successfully installed, and it's powered (either by battery or electricity); press this button for about 3 seconds to turn on the Device, and if you want to turn it off, please press this button for another 3 seconds. Double-pressing the power button will switch the work mode to the power bank mode.
- RESET Button (hole): It's the button to restore the Device to its factory defaults. With the Device powered on, use a pin to press and hold the RESET button (hole) for about 5 seconds, until the LED screen is off and later displays "TP-LINK"; then release the button

and wait the Device to reboot and restore its factory default settings.

- > **SIM Card Slot:** It's where to insert your SIM card.
- > Micro SD Memory Card Slot: It's where to insert your micro SD memory card.
- > **USB Port:** It can charge for other devices via the USB cable.

Chapter 2. Hardware Installation


2.1 Environment Requirements

- > Place the Device in a well-ventilated place far from any heater or heating vent
- > Avoid direct irradiation of any strong light (such as sunlight)
- > Keep at least 2 inches (5 cm) of clear space around the Device
- Operating Temperature: 0°C~40°C (32°F~104°F)
- > Operating Humidity: 10%~90%RH, Non-condensing

2.2 Hardware Installation

Install SIM card

Open the card slot cover as shown, then slide the SIM card into the slot until you hear a clicking sound.



P Note:

- 1. SIM card not provided by TP-LINK.
- 2. Micro or Nano SIM cards should be converted using provided SIM card trays.
- 3. Before the SIM card inserted, please make sure that the M5360 is power off and not charged.


Turn on the M5360

Hold the power button until the screen appears as shown below. (You can also hold the power button to turn off the M5360).




Charging your M5360

Via the power adapter



Via the computer USB



PNote:


Your M5360 has been fully charged when the lighting symbol () of battery icon disappeared.

Charging Your Device

M5360 can be used as a 5200mAh power bank to charge smart phones and tablets by using one of the following two modes.

Double-tapping the power button can switch between the two modes.


Simultaneous 3G sharing and charging



Solution Note:

In this mode, M5360 will become hot as a result of high-load usage. When the M5360 overheats, it will automatically turn off to protect itself from damage. After the heat has dissipated, you can turn it on and use it normally.

Charging only (Strongly recommended to save power)



P Note:

The M5360 can't be charged and charge other devices at the same time.

Accessing the Micro SD Card

If M5360 is connected to a computer with an USB cable, you can access its micro SD memory card just as access a hard disk.

- 1) Connect one end of the USB cable to the micro USB port of M5360 and the other end to the USB port of your PC.
- 2) If there appears the Found New Hardware Wizard window, please click Cancel to ignore it.
- 3) Double click Computer icon on your desktop. The inserted micro SD card is displayed as removable disk in file explorer (Here we use Removable Disk (F:) as an example). Double click to access the micro SD card just as access a hard disk.

Chapter 3. Quick Installation Guide

This chapter will guide you to quickly set up the basic functions for your M5360.

3.1 System Requirements

- > SIM card with Internet access enabled.
- > Computer supports only the 2.4GHz wireless band.
- > Web browser, such as Mozilla Firefox, Internet Explorer, Google Chrome, Apple Safari, etc.

3.2 TCP/IP Configuration

The default IP address of the M5360 is 192.168.0.1, and the default Subnet Mask is 255.255.255.0, which values can be changed as you desire. In this guide, we use all the default values for description, and take the configuration in Windows 7 for example. While, Pads or Wi-Fi cellphones by default obtain IP address and DNS server address automatically, so you can just skip this step and continue with the <u>3.3 Connect to the Internet</u>.

P Note:

Before configuration, please make sure your computer has been equipped with a wireless network adapter.

> Obtain an IP address automatically

- Set up the TCP/IP Protocol in "Obtain an IP address automatically" mode on your PC.
 Please refer to <u>Appendix B: Configuring the PC</u> for the detailed instructions.
- 2) Then the built-in DHCP server will assign an IP address for the PC.
- > Configure the IP address manually
- Set up the TCP/IP Protocol for your PC. Please refer to <u>Appendix B: Configuring the PC</u> for the detailed instructions.
- Configure the network parameters. The IP address is 192.168.0.X (X stands for any number from 2 to 254), Subnet Mask is 255.255.255.0, and Gateway is 192.168.0.1 (the device's default IP address).

3.3 Connect to the Internet

P Note:


To log in the Device's web-management page, you need to first connect to the wireless network of the Device.

- 1. Click the icon $\stackrel{\text{dl}}{=}$ at the bottom of your desktop.
- 2. Click the refresh button 5, and then select the SSID of M5360 and then click **Connect**.



Note:

The default SSID (also called Wireless Network Name) of the device is **TP-LINK_M5360_XXXXXX.** (XXXXXX is the last 6 characters of the device's MAC address.)



3. Enter the wireless password found on the M5360's back cover, and then click OK.



4. When **Connected** appears behind the SSID of M5360, you've successfully connected to its wireless network.

Solution Note:

After successful connection to M5360 (with a SIM card inserted), you can enjoy the 3G mobile connection instantaneously. If not, please refer to <u>FAQ</u> and retry.

3.4 Quick Setup

1. Open a web-browser, enter the default address **192.168.0.1** in the address field and then

press **Enter**. When the login window appears, enter **admin** (in lower case letters) for Password, and then click the **Log in** button or press the **Enter**.

TP-LINK [®]	_	M5360
Username:	admin	
Password:		
	Log in	

Figure 3-1 Login Windows

P Note:

If the above screen does not pop-up, it means that your Web-browser has been set to a proxy. Go to **Tools menu > Internet Options > Connections > LAN Settings**, in the screen that appears, cancel the Using Proxy checkbox, and click **OK** to finish it.

2. After successful login, there will appear the Status page. Click Wizard to configure the basic network settings for accessing network. Click **Next** to continue.

TP-LINK [®]		~			S 😁 🗎 S 🗆 🖗
		\odot	\sim	Ϋ́	
	Status	Wizard	SMS	Advanced	
Start	→ Dial-up Settings	➡ Wire Setti		Finish	
This wizard will certain function	guide you to config or parameters, clic	ure the basic n k Advanced .	etwork settings	for accessing netwo	ork. Click Next to continue. For detailed configuration of a
					Next

Figure 3-2 Wizard - Start

 On the Dial-up Settings page shows the ISP information of the SIM card inserted. Click Next to continue, if you are sure the information is correct. You can also click Create to create a new profile.

	O Wizard	SMS A	Y ¶ dvanced		ج 🖷 🗆 (؟) الب 🗳	?
Start → Dia Set	up ings → Wireless Settings	Fin	ish			
Profile L	st: China Unicom(D)	•				
APN Ty	oe: Static	•				
AF	N: 3gnet					
Usernar	ne:					
Passwo	rd:					
Authentication Ty	e: Auto	•				
			Create	Back	Next Cancel	

Figure 3-3 Wizard – Dial-up Settings

 On the Wireless Settings page, you can create a unique and easy-to-remember wireless network name (SSID) as well as Wireless Password, or you can keep it default. Then click Next to continue.

TP-LINK [®]						⊇ @ ⊪ ≌	● 奈 ?
	\bigcirc	\odot	\simeq	۲P			
	Status	Wizard	SMS	Advanced			
Start →	Dial-up Settings	➡ Wireles Setting		Finish			
Wireless Netw	ork Name (SSID): TP-LINK_M5	360_EC8902				
WPA-PSK/WPA	2-PSK AES Ke	y: 00002448		(8 to 63 ASCII cha	racters or 8 to 64 hexaded	cimal characters)	
					Back	Next	Cancel

Figure 3-4 Wizard – Wireless Settings


5. On the Finish page, please double-check your settings. If all the parameters are verified, click **Finish** to complete the Wizard; if there is anything wrong, you can click **Back** to re-configure it.

TP-LINK'		0		۲I			∥ (\$) ⊂ ■	∻ ?
	Status	Wizard	SMS	Advanced				
Start → Confirm the parame quit the configuratio			igs	Finish ick Back to retur	n to the previous pages to	modify parameters	. Click Cance	l to
	Profile Name	e: China Unic	om(D)					
		l: 3gnet						
	Username	Empty						
	Password	l: Empty						
Au	uthentication Type	: None						
Wireless Netv	vork Name (SSID)	: TP-LINK_M	5360_EC8902					
WPA-PSK/WP/	42-PSK AES Key	c 00002448						
					Back	Finish	Canc	el

Figure 3-5 Wizard – Finish

Chapter 4. Device Configuration

After the successful login to the web-based management page of M5360, you will see the main menu listing **Status**, **Wizard**, **SMS** and **Advanced** on the top. In the following parts, these items will be explained in details, about their respective functions and configurations.






4.1 Status

The Status page displays the current status information about the device. All information is read-only.

TP-LINK [®]	-					S = S = ?
	\bigcirc	\odot	\simeq	۲I		
	Status	Wizard	SMS	Advanced		
Connection Status	_	_	_	_		
Connection Status	: Connected	IP A	ddress: 172.1	8.134.80	Primary DNS Server: 221.6.	4.66
Secondary DNS S	erver: 58.240.57.	33 Dial	-up Type: Auto)	SIM Card Status: Ready	
Network Type: UN	ITS					
Statistics						
Current Data Reco	eived: 280.41K				Current Data Sent: 49.17K	
Online Time: 4Min	nutes				Total Data: 1.45M	Data Correction
WiFi Status						
Wireless Network	Name (SSID): TP	-LINK_M5360_	EC8902		Channel: Auto	
Encryption Type: Y	WPA/WPA2-PSH	<			Current Clients: 1	Vireless Settings
						Refresh



- Connection Status: Displays the device's current connection status, including the connection and SIM card status, Dial-up and network type, IP address, primary and secondary DNS server.
- Statistic: Displays the device's statistics, including current received and sent data, online time and total data used.
- WiFi Status: Displays the device's current wireless settings, including SSID, channel, encryption type and current Wireless clients.

Click **Data Correction** to correct the accumulate data used. If the data statistics is different from that your ISP provided, please click **Data Correction** button, and input the data statistics your ISP provided to correct the accumulate data used.

Click Wireless Settings to head for the Wireless Basic Settings page and configure it.

Click **Refresh** to get the status information updated.

4.2 Wizard

Please refer to <u>3.4 Quick Setup</u>.

4.3 SMS

🞯 New Message
& Inbox
合 Outbox
🕞 Drafts
🔀 SMS Settings

Figure 4-3 SMS Menu

There are five submenus under the **SMS** tab (as shown in Figure 4-3): **New Message**, **Inbox**, **Outbox**, **Drafts** and **SMS Settings**. Click any of them, and you will be able to configure the corresponding functions.

4.3.1 New Message

TP-LINK [®]	~	-	-		6	2 ml (S) 📼 🗎 奈 ?
		\odot	\simeq	۲I		Logout
	Status	Wizard	SMS	Advanced		
🞯 New Message	New Message					
🛃 Inbox		Phone I	Number:		~	
🔒 Outbox			Content:			
Drafts		,	Soment.			
🧙 SMS Settings		Charact	ers Left: 160(0)	<u>~</u>	
					Sen	d Save

Figure 4-4 New Message

- > **Phone Number:** Enter the receiver's cellphone number.
- > **Content:** Text your message in this box.

Click **Send** to send the message.

Click Save to save the message in the Drafts box.

4.3.2 Inbox

TP-LINK [®]					S a 🕲 🖂	● 奈?
		\odot		Y I		
	Status	Wizard	SMS	Advanced		
😋 New Message	Inbox					
	Index State	us Rec	eived	Phone Number	Content	Select
🖾 Inbox	1 🖂	13-05-14	08:01:17	10010	It's great! We have a wonderful day.	
	2 🖂	13-05-14	08:01:17	10010	Happy birthday!	\odot
🛕 Outbox	3 🖂	13-05-13	08:32:39	10010	Don't worry. Everything will be fine.	
	4 🖂	13-05-13	08:32:39	10010	How's your date?	0
Drafts	5 🖂	13-05-12	08:52:36	10010	When will you arrive?	0
	6 🖂	13-05-12	08:52:36	10010	Sorry. I'd love to but I can't.	0
SMS Settings	Messages/Free	:6/44			٩ (1	
					Select All Refresh	Delete

Figure 4-5 Inbox

- > Index: The index of the message.
- Status: means the message has been read. means the message hasn't been read yet.
- > **Received:** Shows the date and time when the message was received.
- > Phone Number: Shows the cellphone number that sent this message.
- > **Content:** Click to unfold and read the detailed content of the message.
- > **Select:** Select the message(s) for deletion.

Click Select All to select all of the messages.

Click **Refresh** to refresh the inbox, and get any new message(s).

Click **Delete** to delete the message(s) selected.

Select All

🛥 । 🕲 🖭 🕾 ?

.

Refresh

Delete

4.3.3 Outbox					
TP-LINK [®]	Status	O Wizard	SMS	Advanced	
😋 New Message	Outbox				
🕹 Inbox	Index Messages/Fre	Delivered ee:0/50	Phone	e Number	Content
습 Outbox					
Drafts					
SMS Settings					

Figure 4-6 Outbox

- > Index: The index of the message.
- > Delivered: Shows the date and time when the message was sent.
- Phone Number: Shows the cellphone number that the message was planned to be sent to.
- > **Content:** Click to unfold and read the detailed content of the message.
- > **Select:** Select the message(s) for deletion.

Click **Select All** to select all of the messages.

Click **Refresh** to refresh the inbox.

Click **Delete** to delete the message(s) selected.

4.3.4 Drafts

TP-LINK [®]						ビ 💷 🕲 🖭 🛜 ?
	\bigcirc	\odot		۲I		
	Status	Wizard	SMS	Advanced		
🞯 New Message	Drafts					
🛃 Inbox	Index 1	Phone N 100		Hello, how's your week	Content kend?	Select
Gutbox	Messages/Fre	e:1/49				
Drafts						
SMS Settings						
					Select All	Refresh Delete

You can review the unsent saved message(s) on this page.

Figure 4-7 Drafts

- > **Index:** The index of the message.
- Phone Number: Shows the cellphone number that this message was planned to be sent to.
- Content: Click to unfold and read the detailed content of the message(s), or for further edition and delivery (as shown in Figure 4-8).
- > **Select:** Select the message(s) for deletion.

Click Select All to select all of the messages.

Click Refresh to refresh the drafts.

Click **Delete** to delete the message(s) selected.

TP-LINK [®]	Generation	O Wizard	SMS	Y I Advanced		∑ III ()	● 全 ■ 奈 ?
🞯 New Message	Edit Message		Cimo	Advanced			
🛃 Inbox		Phone Nu		8 lo, how's your	weekend?	*	
Outbox		Co	intent:	io, now 5 your	weekend.		
SMS Settings		Characters	s Left: 133(*)		Ŧ	
				< <bac< td=""><td>k Delete</td><td>Send</td><td>Save</td></bac<>	k Delete	Send	Save

Figure 4-8 Edit Message (Drafts)

4.3.5 SMS Settings

On this page, you can do the following settings:

TP-LINK°		~	_	4.50		S = S = S - S = S = S - S = S = S = S =
	\bigcirc	\odot		۲I		
	Status	Wizard	SMS	Advanced		
🞯 New Message	Message Sett	ings				
🕹 Inbox	M	Message essage Center N	Center: Disab	le	V	
👍 Outbox	Save th	he Delivered Me	ssages: Enab		T	
Drafts	Auto	Replace Old Me	ssages: Enab	le	Ŧ	
SMS Settings						
						Save

Figure 4-9 Settings

- Message Center: Disabled by default. It's recommended to keep the default setting. If you want to manually set the Message Center Number, please select Enable.
- Message Center Number: When the Message Center is enabled, you can enter the Message Center Number of the local ISP. If you enter a wrong number, the SMS would be affected and not properly used.
- > Save the Delivered Messages: Enable it to automatically save the delivered messages in

the Outbox.

Auto Replace Old Messages: If enabled, it will automatically delete the oldest message and save the new one when the Outbox or Drafts box is full. If disabled, you need to manually delete the old messages to save the new ones when the Outbox or Drafts box is full.

Click **Save** to make your settings take effect.

4.4 Advanced




Figure 4-10 Advanced Menu

There are four submenus under the **Advanced** tab (as shown in Figure 4-10): **Dial-up**, **Wireless**, **DHCP Server** and **System Tools**. Click any of them, and you will be able to configure the corresponding functions.

4.4.1 Dial-up



Figure 4-11 Dial-up Menu

4.4.1.1. Dial-up

Dial-up Settings page allows you to do the following configurations.
--

TP-LINK [®]) lin 🖸	\$ 🗆 🗎 ጵ ?
	\bigcirc	\odot	\simeq	۲P			Logout
	Status	Wizard	SMS	Advanced			
iii Dial-up	Dial-up Setting	s					
Dial-up		Profi	le List: Non	e(D)	•		
Profile Management		Network S	Status: Disc	onnected			
Network Mode		Dial-up	Type: Auto)	$\overline{\mathbf{v}}$		
PIN Management		Data Ro	aming: Disa	able	▼ (Da	ata service is not allowed when roa	aming)
Auto-unlock PIN							
察 Wireless							
DHCP Server							
💋 System Tools							
							Save

Figure 4-12 Dial-up Settings

- Profile List: A list of profile(s). Select the profile of your SIM card currently inserted in the device.
- > Network Status: Shows whether the Internet is connected or disconnected at present.
- Dial-up type: The device provides two types of dial-up Auto and Manual. Please select the dial-up type as you need.
 - Auto: The device will automatically establish connection once it's started. During the process, if your Internet connection is terminated due to some exterior reasons, the device would automatically attempt connection until it's successful. This option is suggested, if you have the network service paid by month.
 - **Manual:** When you start the device and your computer, or when the connection is terminated during the process, you need to manually dial up for connection in here. If you have the network service paid by hour, this option is suggested.
- Data Roaming: It is disabled by default. If disabled, data service is not allowed when roaming. If enabled, data service is allowed when roaming, but may incur significant roaming charges.

Click **Save** to save the above settings and have them take effect.

4.4.1.2. Profile Management

You can manage your profile on this page.

TP-LINK °	-					S 💷 🕲 🕆 🤉
	\bigcirc	\odot	\simeq	۲P		Logout
	Status	Wizard	SMS	Advanced		
🛄 Dial-up	Profile Mana	gement				
Dial-up		Pro	file List: Chin	a Unicom(D)	∇	
Profile Management		Profile	e Name: China	a Unicom(D)		
Network Mode		AP	N Type: Stati	с	T	
PIN Management Auto-unlock PIN			APN: 3gne			
		Us	ername:			
🛜 Wireless			issword:			
DHCP Server		Authenticatio		P	~	
💋 System Tools						
						Create

Figure 4-13 Profile Management

- Profile List: A list of profile(s). Select the profile of your SIM card currently inserted in the device, and then you can view the related information of it. If you find any parameters wrong, you can click Create to create a new profile with the right settings (as shown in Figure 4-14).
- > **Profile Name:** Displays the name of the profile you've selected.
- APN Type: Displays the type of your APN, either Dynamic or Static. Dynamic means the device have dynamic APN, which needs not to be specified. Static means you specify your APN manually.
- > **APN:** Displays the Access Point Name provided by your ISP.
- > Username/Password: Displays the User Name and Password provided by your ISP.
- > Authentication Type: Displays the specific authentication type your ISP required.
 - **None:** Means no authentication is required.
 - **CHAP:** Means your ISP required Challenge Handshake Authentication Protocol, which allows the device to establish authentication with the peer using three handshakes and checking the peer identity periodically.
 - **PAP:** Means your ISP required Password Authentication Protocol, which allows the device to establish authentication with the peer using two handshakes.

TP-LINK [®]		\odot	\simeq	۲P			S 111 S	. ⊂ • ?
	Status	-	SMS					Logout
	Status	Wizard	5105	Advanced				
🛄 Dial-up	Create Profile							
Dial-up		Profi	le Name:					
Profile Management		A	PN Type: Stati	с	~			
Network Mode			APN:					
PIN Management Auto-unlock PIN		Us	sername:					
		P	assword:					
Wireless		Authenticati	on Type: CHA	P	~			
DHCP Server								
💋 System Tools								
						- 1	Cancel	Save

Figure 4-14 New Profile

4.4.1.3. Network Mode

TP-LINK [®]						S 🖷 🖱 🖓 🖓
	\bigcirc	\odot	\geq	۲I		
	Status	Wizard	SMS	Advanced		
iii Dial-up	Network Mod	le Setting				
Dial-up		Network	Status: Conr	ected		
Profile Management		Network	K Mode: Auto		•	
Network Mode						
PIN Management						
Auto-unlock PIN						
察 Wireless						
DHCP Server						
🔑 System Tools						
						Save

Figure 4-15 Network Mode Settings

- > Network Status: Shows whether the Internet is connected or disconnected at present.
- Network Mode: The device supports three modes of network connection Auto, 2G only and 3G only. You can choose the appropriate mode after disconnecting the network. If your SIM card supports GSM, please select 2G only; if your SIM card supports WCDMA, please select 3G only; if you are not very sure about it, please select Auto and then the device will detect it automatically.

Click Save to save your settings.

4.4.1.4. PIN Management

You can management your PIN code on this page.

TP-LINK °						₽	⊪ 🕲 🖭 ବି ?
	\bigcirc	\odot	\simeq	۲P			
	Status	Wizard	SMS	Advanced			
🛄 Dial-up	PIN Managem	ient					
Dial-up	S	IM Card Current	Status: PIN d	isabled			
Profile Management		PIN Manag	gement: Enab	le	-		
Network Mode			PIN:				
PIN Management		Remaining At	tempts: 3				
Auto-unlock PIN							
Wireless							
DHCP Server							
>> System Tools							
							Apply

Figure 4-16 PIN Management

- > SIM Card Current Status: Shows whether your PIN function is enabled or disabled.
- PIN Management: You can select whether to enable PIN function or not. Once the PIN function is enabled, every time you start the device with this SIM card inserted, you need to enter the PIN code; while if you go to enable the Auto-unlock PIN function, it could save you this trouble.
- > **PIN:** You can set a PIN code, which requires 4-8 digits.
- Remaining Attempts: Shows how many attempts there are left for you to try entering the PIN code after you failed to enter the right one. You have 3 attempts at most. If you accidentally fail in three attempts, the PIN will be locked and you will be required to enter the PUK code that is written on your SIM card (as shown in Figure 4-17).

If the current status of PIN is disabled, you can select **Enable** and set a PIN code, and then click **Apply** to make your settings take effect. While, if the SIM card's current status is PIN enabled and verified, you can select **Disable** and enter the current PIN code, or select **Modify** and enter the required parameters to set a new PIN code, and then click **Apply** to make your settings take effect.

TP-LINK [®]		\odot		۲I		⊻ ⊪ (5) æ 🗎 ∻ ?
	Status	Wizard	SMS	Advanced		
iii Dial-up	PIN Managem	ient				
Dial-up	S	IM Card Current	Status: PUK	required		
Profile Management			PUK:			
Network Mode		N	ew PIN:			
PIN Management		Confi	rm PIN:			
Auto-unlock PIN		Remaining At	tempts: 10			
Wireless						
DHCP Server						
💋 System Tools						
						Unlock

Figure 4-17 PIN Configuration - PUK Decode

A PUK (PIN Unlocked Key), also known as Personal Unlock Code (PUC), is used in 3GPP mobile phones to reset a personal identification number (PIN) that has been lost or forgotten. The PUK is a SIM-specific code assigned by the service provider. If a user does not know his or her PUK and is prompted for it, it should be obtained from the service provider.

On the page as shown in Figure 4-17, first enter the PUK code and then set a new PIN code to unlock your SIM card as well as any device with it inserted.

TP-LINK [®]	-			_		S 🖷 S 🕾 🗎 ጵ ?
	\bigcirc	\odot	\simeq	۲P		
	Status	Wizard	SMS	Advanced		
🛄 Dial-up	Auto-unlock I	PIN				
Dial-up	Auto-unlo	ck PIN on Powe	ring On: Disat	ble	•	
Profile Management			PIN: 1234			
Network Mode						
PIN Management						
Auto-unlock PIN						
🛜 Wireless						
DHCP Server						
🔑 System Tools						
						Save

4.4.1.5. Auto-unlock PIN



Logou

- > Auto-unlock PIN on Powering On: Select to enable or disable this function.
- > PIN: If you enable the Auto-unlock PIN on Powering ON function above, please enter the appropriate PIN code of your SIM card in this field. When the PIN code is required upon device restarting, it will be validated automatically once. If validation failed, please go to **PIN Management** page to input another PIN code.

Click Save to save your settings.

4.4.2 Wireless




Figure 4-19 Wireless Menu

Wireless Settings can prevent any intruders from connecting your wireless network, occupying your network resources, hacker-overhearing and hacker-attacking, and thus enhance the security of your wireless network.

4.4.2.1. Basic Settings

/ireless basic settin	gs enable	e you to co	onfigure	e your wireless p	ara	meters.
TP-LINK [®]) Status	O Wizard	SW2	Y I Advanced		🗎 至 📎 III 🖾
🔛 Dial-up	Wireless Basi	ic Settings				
察 Wireless	Wireless	Network Name	(SSID):	TP-LINK_M5360_EC8902		
Basic Settings	E	Enable SSID Bro	adcast:	Enable	•	
MAC Filter		Region:		United States	•	
Wireless Status		C	Channel:	Auto	•	
DHCP Server		Wireless	s Mode:	11bgn Mixed	•	
		Wireless S	ecurity:	WPA-PSK/WPA2-PSK	•	
🎾 System Tools		Wireless Pa	ssword:	12345678		(At least 8 characters and case sensitive)
	1	WiFi Auto-disabl	le Time:	15		minutes
						_

Figure 4-20 Wireless Basic Settings

Wireless Network Name (SSID): SSID is short for Service Set Identification, which is for you to distinguish the different wireless network. The default SSID of this device is TP-LINK_M5360_XXXXXX (XXXXXX stand for the last 6 characters of the MAC address of the device.) You can rename it as your preference, but the value is limited to 32 characters at most and also it is case-sensitive (For example, TEST is NOT the same as test.). Later on it will displays in the wireless network list searched by your devices.

- Enable SSID Broadcast: Select to enable or disable this function. When wireless clients search the local area for wireless networks to associate with, they will detect the SSID broadcast by the device. If you Enable SSID Broadcast, the Wireless device will broadcast its name (SSID) on the air; otherwise, you have to manually type in the SSID and then you can join its network.
- Region: Select your region from the drop-down list. This field specifies the region where the wireless function of the device can be used. It may be illegal to use the wireless function of the device in a region other than one of those specified in this field. If your country or region is not listed, please contact your local government agency for assistance.
- Channel: This field determines which operating frequency ranging from 1~11 will be used. If you select Auto, then the device will choose the best channel automatically. It is not necessary to change the wireless channel unless you notice interference problems with another nearby access point.
- Wireless Mode: You are provided with two wireless modes here: 11bg Mixed and 11bgn Mixed. The default wireless mode is 11bgn Mixed. If your wireless network card didn't work well in 11bgn Mixed mode, try 11bg Mixed mode.
- Wireless Security: You are provided with two modes of wireless security here: Not Secured, WPA-PSK/WPA2-PSK.
 - WPA-PSK/WPA2-PSK: It's the WPA/WPA2 authentication type based on pre-shared pass phrase. It's easy to set and secure to use. So it's perfect for SOHO users.

Wireless Password: The default WPA key is the last 8 characters of IMEI. You can keep it default or enter at least 8 ASCII characters or 8 hexadecimal characters as your new Wireless Password.

WiFi Auto-disable Time: If no clients connect to the device's wireless network in a period of time (15 minutes by default), the Wi-Fi will be shut down. You can press the power button to resume the Wi-Fi.

Click **Save** to save your settings.

4.4.2.2. MAC Filter

The Wireless MAC Address Filtering feature allows you to control the wireless stations accessing the device, which depends on the station's MAC addresses. MAC Address is the physical address of the wireless stations, usually in the format of XX-XX-XX-XX-XX-XX format (X is any hexadecimal digit).

		M5360	SG MOI		i, 5200mAh Powe	er barrk USE	Guide
TP-LINK [®]		\odot		۲P		() in ()	■ 奈? Logout
	Status	Wizard	SMS	Advanced			
 Dial-up Wireless Basic Settings MAC Filter Wireless Status DHCP Server DHCP Server System Tools 	Wireless MAC MAC Address	iress: 14-CF-92- 1:	Disable lients with MA		MAC Address2: MAC Address4: MAC Address6: MAC Address8: MAC Address10:	ss the device.)	Save

Figure 4-21 Wireless MAC Filter

- Wireless MAC Address Filter: Select to Enable or Disable the MAC filter function of the device. The below settings will take effect only when you select Enable.
- Your MAC Address: Displays the MAC address of your client(s) currently wirelessly connected to the device.
- > MAC Address List: A List of MAC addresses will be allowed to access the device.

Click **Save** to save your settings.

4.4.2.3. Wireless Status

The Wireless Status page displays the basic information about the Wireless client(s) that are currently connected to the device.

TP-LINK [®]	Status	O Wizard	SMS	Y Advanced		S 1 (C E) ? ?
🛄 Dial-up	Wireless Stat	us acted wireless cli	ont numbors: 1	,		
Wireless Basic Settings		ID 1 2		-	MAC Address 10-68-3F-8A-17-49 84-4B-F5-39-FF-91	
MAC Filter Wireless Status						
DHCP Server						
🌽 System Tools						
						Refresh

Figure 4-22 Wireless Status

- > **ID:** The index of the Wireless Client.
- > MAC Address: The MAC address of the Wireless client.

Click **Refresh** to update the amount of the Wireless clients and their information.

4.4.3 DHCP Server




Figure 4-23 DHCP menu

The Device is set up by default as a DHCP (Dynamic Host Configuration Protocol) server, which provides the TCP/IP configuration for all the wireless clients that are connected to the device in the LAN.

4.4.3.1. Basic Settings

TP-LINK [®]	~	~	_			S = () - () - () - () - () - () - () - ()
	\bigcirc	\odot	\simeq	۲P		
	Status	Wizard	SMS	Advanced		
iii Dial-up	Basic Setting	s for DHCP Ser	ver			
🔿 Wireless		IP A	ddress: 192	.168.0.1		
		Subne	t Mask: 255	.255.255.0		
DHCP Server		DHCP	Server: Ena	ble	•	
Basic Settings		Start IP A	ddress: 192	.168.0.100		
Client List		End IP A	ddress: 192	.168.0.199		
🔑 System Tools		Leas	e Time: 120			minutes (Ranging from 1 to 2880, the default value is 120)
		Primary DNS	Server: 192	.168.0.1		(optional)
		Secondary DNS	Server: 0.0.	0.0		(optional)
						Save

Figure 4-24 Basic Settings

- IP Address: The IP address of the device, which is used to log in its web-based management page. The default value is 192.168.0.1.
- Subnet Mask: An address code that determines the size of the network. Normally use 255.255.255.0 as the subnet mask.
- DHCP Server: You can select to enable or disable the DHCP server. If you disable the server, you must have another DHCP server within your network, or else you must configure the IP address of the host(s) manually.
- Start IP Address: This field specifies the first address in the IP address pool. 192.168.0.100 is the default start IP address.
- End IP Address: This field specifies the last address in the IP Address pool. 192.168.0.199 is the default end IP address.
- Lease Time: It is the length of time a network user will be allowed to keep connecting to the device with the current IP address (that is assigned by the DHCP server). Enter the amount of time, in minutes, that the IP address will be "leased". The time range is 1~2880 minutes. The default value is 120 minutes.
- Primary DNS Server: Input the DNS IP address provided by your ISP. It is optional. The default primary DNS server IP is 192.168.0.100.
- Secondary DNS Server: Input the IP address of another DNS server if your ISP provides two DNS servers. It is optional. The default secondary DNS server IP is 192.168.0.199.

Click Save to save the changes.

Solution Note:

To use the DHCP server function of the Device, you should configure all the clients in the LAN

as "Obtain an IP Address automatically" mode.

4.4.3.2. Client List

On this page, you can view the information about the clients attached to the device. All the information is read-only. You cannot change any of the values on this page.

TP-LINK [®]	-					🗳 💷 🖉 🗖	■ 奈 ?
	\bigcirc	\odot	\geq	¥!			Logout
	Status	Wizard	SMS	Advanced			
iii Dial-up	Current Clier	nt List					
察 Wireless	ID 1	Client Name tplink3050		MAC Address 14-CF-92-13-6D-78	IP Address I 192.168.0.100	Lease Residual 01:17:32	
DHCP Server							
Basic Settings							
Client List							
🔑 System Tools							

Figure 4-25 Clients List

- > **ID:** The index of the DHCP Client.
- > Client Name: The name of the DHCP client.
- > MAC Address: The MAC address of the DHCP client.
- > **IP Address:** The IP address the device has assigned to the DHCP client.
- Lease Residual : The rest lease time for the IP address assigned to the DHCP client. The DHCP client will automatically apply to lengthen the lease time before the dynamic IP address expires.

4.4.4 System Tools

🔑 System Tools
Configuration
Restore Factory
Modify Password
Reboot
System Log
About Device

Figure 4-26 System Tools menu

Under **System Tools** menu, you can do such configurations as backing up or uploading a configuration file of the device, restoring all the settings of the device to its factory defaults, modifying the password for your login, rebooting the device, and checking some information about the device. As follows, we will explain them in details.

4.4.4.1. Configuration

On this page, you can back up the configuration of the device to file, or upload a configuration file to the device.

TP-LINK°						s 🔊 🗎 🗩 🥐 👘
	\bigcirc	\odot	\simeq	YP		Logout
	Status	Wizard	SMS	Advanced		
Dial-up	Configuration	n Management				
察 Wireless		up Configuration	-	ckup	Browse Upload	
DHCP Server	0	olda oomigaraa			Dionse Opioud	
System Tools						
Configuration						
Restore Factory						
Modify Password						
Reboot						
System Log						
About Device						

Figure 4-27 Configuration Management

- Backup Configuration to File: Click Backup to save the configuration file in your computer, for later necessary use. It's strongly recommended to back up the old configuration file before firmware upgrade or new configuration file upload, in case that during those process it might get the original configuration lost.
- Upload Configuration File: Click Browse... to locate the config.bin file or directly enter its location file, and then click Upload to upload the configuration file.

4.4.4.2. Restore Factory

You can restore the device to its factory default settings, when necessary.

M5360 3G Mobile Wi-Fi, 5200mAh Power Bank User Guide

TP-LINK [®]		~			S 🗐 🗐 🖓 🖬 🔶 🤆
	\bigcirc	\odot	\simeq	YP	Logout
	Status	Wizard	SMS	Advanced	
iii Dial-up	Restore to Fa	ctory Defaults			
察 Wireless	Rest	ore to Factory D	efaults: Re	store	
DHCP Server					
🔑 System Tools					
Configuration					
Restore Factory					
Modify Password					
Reboot					
System Log					
About Device					

Figure 4-28 Restore to factory defaults

Restore to Factory Defaults: Click Restore to reset all configuration settings to their default values. All of the settings you have saved will be lost when the default settings are restored.

You can restore the following factory default values:

- The default login Password: admin
- The default IP Address: 192.168.0.1
- The default Subnet Mask: 255.255.255.0
- The default SSID: TP-LINK_M5360_XXXXXX (XXXXXX is the last 6 characters of the device's MAC address). Please refer to the label on the rear cover of the device for the default SSID.
- The default Wireless Password: Please refer to the label on the rear cover of the device for the default wireless password.

4.4.4.3. Modify Password

It is strongly recommended that you change the factory default login password of the device.

TP-LINK[®]	-					🖾 💷 🕲 🖂 📓 😓 🤉
	\bigcirc	\odot	\simeq	Y I		Logout
	Status	Wizard	SMS	Advanced		
🛗 Dial-up	Modify Login	Password				
察 Wireless	l	Jsemame and pa	assword can o	ontain between 1 – 15	5 characters and may no	t include spaces.
DHCP Server		Old User Old Pa				
🔑 System Tools		New User	Name:			
Configuration		New Pa	ssword:			
Restore Factory Modify Password		Confirm New Pa	ssword:			
Reboot						
System Log						
About Device						
						Save Clear

Figure 4-29 Modify Login Password

- Old Password/User Name: The old password/User Name that is used to log in of the device.
- New Password/User Name: The new password/User Name you want to set for the login of the device.
- **Confirm New Password:** Enter the new password again for confirmation.

Click **Save** when you finish the setting.

Click Clear to clear all the values you have already set, and then you can reset it.

P Note:

The new password must not exceed 14 characters in length and not include any spaces.

4.4.4.4. Reboot

TP-LINK [®]	-				🖾 💷 🕲 🖉 🖿 🗢 🕇
		\odot	\simeq	۲P	Logout
	Status	Wizard	SMS	Advanced	
🛄 Dial-up	Reboot the D	evice			
察 Wireless		Reboot the	Device: Ret	poot	
DHCP Server					
🔑 System Tools					
Configuration					
Restore Factory					
Modify Password					
Reboot					
System Log					
About Device					

Figure 4-30 Reboot the Device

Reboot the Device: Click Reboot to get the device rebooted and the saved settings to take effect.

4.4.4.5. System log

This page displays the log information about this device.

TP-LINK [®]						S 💷 🕲 🖓 🖬 🗢 ?
	\bigcirc	\odot	\simeq	۲P		Logout
	Status	Wizard	SMS	Advanced		
🛄 Dial-up	System log					
察 Wireless	Log Type	ALL			Log Level: ALL 🔻	
	ld	Time	Туре	Level	Content	
DHCP Server	909 1:	st day 01:01:46.369	3G	NOTICE	PDP disconnected	
		st day 01:01:46.369	3G	NOTICE	PDP start connecting	
		st day 01:01:43.538	3G	NOTICE	PDP disconnected	
🎾 System Tools		st day 01:01:43.537	3G	NOTICE	PDP start connecting	
		st day 01:01:40.615	3G	NOTICE	PDP disconnected	
Configuration		st day 01:01:40.614	3G	NOTICE	PDP start connecting	
Restore Factory		st day 01:01:37.408	3G	NOTICE	PDP disconnected	
Modify Password		st day 01:01:37.407	3G	NOTICE	PDP start connecting	
		st day 01:01:34.854	3G	NOTICE	PDP disconnected	
Reboot	900 1:	st day 01:01:34.854	3G	NOTICE	PDP start connecting	
System Log						
About Device						
					Copy Clear	Save Refresh

Figure 4-31 System log

- > Log Type: Please select the log type from the drop-down list.
- > Log Level: Please select the log level from the drop-down list.

Click **Copy** to copy the system logs.

Click Save to save the system logs.

Click Clear to clear all the logs.

Click **Refresh** to get the system log information updated.

4.4.4.6. About Device

This page displays the related information about this device, including Model, Firmware Version, Hardware Version, MAC Address, and IMEI.

TP-LINK °					2 m (s) 💷 🛱 ?
		\odot	\simeq	Y I	Logout
	Status	Wizard	SMS	Advanced	
iii Dial-up	The Newest	Software			
less 🔗 Wireless			Model:	M5360	
••		Firmware	Version:	1.1.0 Build 140319 Rel.32900n	
DHCP Server		Hardware	Version:	M5360 v1 00000000	
		MAC A	Address:	08-57-00-12-3C-EE	
🔑 System Tools			IMEI:	864011012597276	
Configuration					
Restore Factory					
Modify Password					
Reboot					
System Log					
About Device					

Figure 4-32 Device Information

- > Model: The Model of the device.
- **Firmware Version:** The current firmware version
- > Hardware Version: The current hardware version.
- MAC Address: The physical address of the device. The value is read-only thus could not be changed.
- IMEI: International Mobile Equipment Identity. Composed of 15 digits, it is unique and thus used to identify individual mobile equipment.

Appendix A: FAQ

FAQ1. What should I do if I cannot log into the web-management page?

- 1) Verify that your device is connecting to the M5360.
- 2) Verify that you entered the correct IP address http://192.168.0.1.
- 3) Verify that your device is obtaining an IP address automatically.

FAQ2. What should I do if I cannot access the Internet?

<u>Tip 1:</u> Check the LAN connection

- 1) Open your web browser and type http://192.168.0.1 in the address bar, and then enter the password, which is admin by default.
- Check if you can log into the web-management page successfully. If not, please refer to FAQ 1 and retry.

Tip 2: Enter the PIN Code

- 1) If "PIN REQUIRED" appears on the screen, please open your web browser and type http://192.168.0.1 into the address bar, then enter the password, which is admin by default.
- 2) Choose "Advanced->Dial-up->PIN Management", then enter the correct PIN code according to your ISP and click Unlock for the settings to take effect.

Tip 3: Check your ISP parameters

- 1) Open your web browser and type http://192.168.0.1 in the address bar, and then enter the password, which is admin by default.
- 2) Choose "Advanced->Dial-up->Profile Management" to verify the parameters are correct with your ISP. These parameters include APN, Dial Number, User name and Password.
- 3) If these settings are not correct, please click Create to create a new profile with the correct parameters, and select Dial-up to choose the new profile from the Profile List.

Tip 4: Check the current network connection mode

- Check the network connection mode on the screen. (The H icon means auto connection mode and the icon means manual connection mode)
- 2) If the current mode is manual, open your web browser and type http://192.168.0.1 into the address bar, then enter the password, which is admin by default.
- 3) Choose "Advanced->Dial-up" to check the network status, if the network is disconnected, click the Connect button to reconnect it.

P Note:

In manual connection mode, the M5360 will automatically lose 3G connection if internet activity idles for 5 minutes, in that case, you can repeat Tip 4 to recover.

Tip 5: Check the SIM card status

- 1) Verify that your SIM card has sufficient credit.
- 2) Verify that your SIM is in your ISP's service area.

FAQ3. How do I restore factory default settings?

Tip 1: Hold the RESET button for about 5 seconds until the screen turns off.

<u>Tip 2:</u> Log into the web-management page, and go to "Advanced->System Tools->Restore Factory".

P Note:

Once M5360 is reset, all the current configurations will be lost and you need to reconfigure it.

Appendix B: Configuring the PC

In this section, we'll introduce how to install and configure the TCP/IP correctly in Windows 7. First make sure your Ethernet Adapter is working, refer to the adapter's manual if needed.


1) On the Windows taskbar, click the **Start** button, and then click **Control Panel**.



2) Click the View network status and tasks.

Adjust your computer's settings View by: Category * System and Security User Accounts and Family Safety Review your computer's status Add or remove user accounts						X
System and Security Review your computer's status		ontrol Panel 🕨	▼ 49	Search Control Panel	l	Q
💎 🖉 Review your computer's status 🛛 🖉 🖓 Add or remove user accounts	Adjust	your computer's settings		View by: Cate	egory 🔻	
 Back up your computer Find and fix problems Wetwork and Internet View network status and tasks Choose homegroup and sharing options Hardware and Sound View devices and printers Add a device Programs Uninstall a program Set up parental controls for any user Add a device Choose homegroup and sharing options Metwork and Internet View devices and printers Add a device Wetwork and	1	Review your computer's status Back up your computer Find and fix problems Network and Internet View network status and tasks Choose homegroup and sharing options Hardware and Sound View devices and printers Add a device Programs	Add or remo Set up paren Appearance Change the the Change desktop digust screen re Clock, Langu Change keyboa Change display ease of Acce et Windows su	we user accounts tal controls for any user and Personalization p background esolution uage, and Region rds or other input meth language ess uggest settings	on	

3) Click the Local Area Connection.



4) Select **Properties** on the Local Area Connection status page.

📱 Local Area Connectio	on Status		x
General			
Connection			
IPv4 Connectivity:		No Internet access	
IPv6 Connectivity:		No Internet access	
Media State:		Enabled	
Duration:		13 days 20:46:47	·
Speed:		100.0 Mbps	
Details			
Activity			-
	Sent —	Received	
Bytes:	8,811,673	49,988,602	
Properties	Disable	Diagnose	
		Close	•

5) In the prompt page that showed below, double click on the Internet Protocol Version 4 (TCP/IPv4).

Local Area Connection Properties
Networking
Connect using:
Realtek RTL8102E/RTL8103E Family PCI-E Fast Etheme
Configure
This connection uses the following items:
Client for Microsoft Networks Good Sector Scheduler
🗹 📮 File and Printer Sharing for Microsoft Networks
Internet Protocol Version 6 (TCP/IPv6)
✓ Internet Protocol Version 4 (TCP/IPv4)
Link-Layer Topology Discovery Mapper I/O Driver
 Link-Layer Topology Discovery Responder
Install Uninstall Properties
Description
Allows your computer to access resources on a Microsoft network.
OK Cancel

6) The following **Internet Protocol Version 4 (TCP/IPv4) Properties** window will display and the **IP Address** tab is open on this window by default.

You have two ways to configure the **TCP/IP** protocol below:

> Setting IP address automatically

Select Obtain an IP address automatically, Choose Obtain DNS server address automatically, as shown in the Figure below:

Internet Protocol Version 4 (TCP/IPv4)		?	x					
General Alternate Configuration								
You can get IP settings assigned automatically if your network supports this capability. Otherwise, you need to ask your network administrator for the appropriate IP settings.								
Obtain an IP address automatically								
Use the following IP address:					٦l			
IP address:								
Subnet mask:								
Default gateway:		1.						
Obtain DNS server address autom	atically							
OUse the following DNS server add	esses:				- I			
Preferred DNS server:								
Alternate DNS server:								
Validate settings upon exit			Adva	anced				
		ОК		Cance	el			

- Setting IP address manually
- a. Select Use the following IP address radio button. And the following items available.
- b. If the Device's LAN IP address is 192.168.0.1, type IP address is 192.168.0.x (x is from 2 to 254), and **Subnet mask** is 255.255.255.0.
- c. Type the Device's LAN IP address (the default IP is 192.168.0.1) into the **Default** gateway field.
- d. Select Use the following DNS server addresses radio button. In the Preferred DNS Server field you can type the DNS server IP address, which has been provided by your ISP.

Internet Protocol Version 4 (TCP/IPv4) Properties	
General	
You can get IP settings assigned automatically if your network supports this capability. Otherwise, you need to ask your network administrator for the appropriate IP settings.	
Obtain an IP address automaticall	у
O Use the following IP address:	
IP address:	192 . 168 . 0 . 241
Subnet mask:	255 . 255 . 255 . 0
Default gateway:	192.168.0.1
Obtain DNS server address automatically	
O Use the following DNS server addresses:	
Preferred DNS server:	202 . 96 . 134 . 133
Alternate DNS server:	· · ·
Validate settings upon exit	Advanced
	OK Cancel

7) Now click **OK** to keep your settings.

Appendix C: Specifications

General		
Standards	IEEE 802.11n, IEEE 802.11b, IEEE 802.11g	
Network Type	3G: HSPA+/HSPA/UMTS	
	2G: EDGE/GRPS/GSM	
Certification	CE, FCC, RoHS	
Dimension	100mm×44.3mm×28.5mm (W x D x H)	
Interface	One Micro USB port, One USB 2.0 port, One SIM card slot, One Micro	
	SD Memory card slot	
Button	Power button, RESET button	
OLED Display	³ ^q ıll/ ² ^q ıll/ ^R ıll Indicates the current network option: 2G/3G/Roam, and signal strength of current network.	
	${oldsymbol{\mathfrak{F}}}$ Indicates the successful network connection.	
	A Means the automatic mode of Internet connection.	
	Means the manual mode of Internet connection.	
	WiFi Displays the Wi-Fi status and the amount of current wireless	
	clients.	
	S Indicates that there is un-read short message(s) and the amount	
	of un-read messages.	
	Displays the remaining battery power.	
	0.0B/s↓ Indicates the download speed of current data transmission.	
	0.0B/s↑ Indicates the upload speed of current data transmission.	
	0.0B Indicates the data used in total.	
Power Supply	Internal 5200mAh Rechargeable Battery	
Wireless		
	WCDMA: 900/2100Mhz	
Band	GSM: 850/900/1800/1900Mhz	
	Download: 21.6Mbps	
Data Rate	Upload: 5.76Mbps	
Frequency	2.4-2.4835GHz	
EIRP		
Security	64/128-bit WEP, WPA-PSK/WPA2-PSK	
Antenna	Internal Antenna	
Environment		
Temperature	Operating : 0°C~40°C	
	Storage: -20℃~60℃	
Humidity	Operating: 10% ~ 90% RH, Non-condensing	
	Storage: 5% ~ 90% RH, Non-condensing	

Appendix D: Glossary

- 802.11n 802.11n builds upon previous 802.11 standards by adding MIMO (multiple-input multiple-output). MIMO uses multiple transmitter and receiver antennas to allow for increased data throughput via spatial multiplexing and increased range by exploiting the spatial diversity, perhaps through coding schemes like Alamouti coding. The Enhanced Wireless Consortium (EWC) [3] was formed to help accelerate the IEEE 802.11n development process and promote a technology specification for interoperability of next-generation wireless local area networking (WLAN) products.
- 802.11b The 802.11b standard specifies a wireless networking at 11 Mbps using direct-sequence spread-spectrum (DSSS) technology and operating in the unlicensed radio spectrum at 2.4GHz, and WEP encryption for security. 802.11b networks are also referred to as Wi-Fi networks.
- 802.11g specification for wireless networking at 54 Mbps using direct-sequence spread-spectrum (DSSS) technology, using OFDM modulation and operating in the unlicensed radio spectrum at 2.4GHz, and backward compatibility with IEEE 802.11b devices, and WEP encryption for security.
- DHCP (Dynamic Host Configuration Protocol) A protocol that automatically configure the TCP/IP parameters for the all the PC(s) that are connected to a DHCP server.
- > ISP (Internet Service Provider) A company that provides access to the Internet.
- SSID A Service Set Identification is a thirty-two character (maximum) alphanumeric key identifying a wireless local area network. For the wireless devices in a network to communicate with each other, all devices must be configured with the same SSID. This is typically the configuration parameter for a wireless PC card. It corresponds to the ESSID in the wireless Access Point and to the wireless network name.
- WEP (Wired Equivalent Privacy) A data privacy mechanism based on a 64-bit or 128-bit shared key algorithm, as described in the IEEE 802.11 standard.
- Wi-Fi A trade name for the 802.11b wireless networking standard, given by the Wireless Ethernet Compatibility Alliance (WECA, see http://www.wi-fi.net), an industry standards group promoting interoperability among 802.11b devices.
- WLAN (Wireless Local Area Network) A group of computers and associated devices communicate with each other wirelessly, which network serving users are limited in a local area.