



USB3.0 Type-C to SD & microSD 4.0 Adapter

Card Reader

UA440C



1× SD/1× microSD
Dual-card Reading



SD UHS-II
312MB/s



Plug & Play

Highlights




SD/microSD

UHS-II 312MB/s
Dual-card Reading



USB 3.0

5 Gbps Super Speed
Data Transfer



Plug & Play

For Various Operating
Systems



Light & Portable

Miniature Design Brings
Infinite Convenience



Scratch Resistant

Aluminum Alloy Case



Durable Design

Braided Cable

Specifications

Hardware

- **Interface:**
 - 1× microSD (TF) Card slot
 - 1× SD card slot
 - * Supports UHS-II with theoretical transfer rates up to 312 MB/s
- **Connector:**
 - 1× USB 3.0 Type-C
- **Connector Input:**
 - 5V/0.3A

Physical

- **Dimension (W×D×H):**
 - 2.14 × 1.35 × 0.45 in
 - (54.4 × 34.2 × 11.5 mm)
- **Case:**
 - Aluminum Alloy Case
- **Cable:**
 - 150 mm (5.9 in) Braided Cable
- **Package Contents:**
 - 1× UA440C
 - 1× Quick Installation Guide

Others

- **Supported Systems:**
 - Mac OS, Windows, iPadOS, iOS, Android, Linux OS, and Chrome OS
- **Supported Maximum Card Size**
 - 2 TB or less
- **Certification:** CE, FCC, RoHS, BSMI
- **Environment:**
 - Operating Temperature: 0°C~40°C (32°F~104°F)
 - Operating Humidity: 10%~90% non-condensing
 - Storage Humidity: 5%~90% non-condensing



For more information, please visit
https://p402dc9ebo3fd.osar.com/products/details/?model=UA440C_V1
or scan the QR code left

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.
Specifications are subject to change without notice. All the brands and product names are trademarks or registered trademarks of their respective holders.
*Port transmission specifications are based on testing results conducted by the TP-Link laboratory. Actual transfer rate is not guaranteed and will vary as a result of device conditions and environmental factors.
©2024 TP-Link